

Benton County Electric System Commercial Customer Load Sheet

Business Name:	
911 Service Location Address:	
Service Location/Customer#:	
Electrical Contact/Phone:	
Voltages Available:	
Single phase 120/240 V	
Three phase 240 V Three phase 120/240 V	
Three phase 120/240 V Three phase 480 V	
Three phase 240/480V	
Three phase 120/208 V	
Three phase 277/480 V	
Service Type: overhead underground	
Available service configurations:	
Single phase- 3 wire_	
Three phase- 3 wire delta	
	4 wire delta
Three phase- 4 wire wye Panel or Switchgear Rating: Interrupting capability (RMS symmetrical amps)	
Panel or Switchgear Rating: Interrupting capability (R	tivis symmetrical amps)
Service Entrance Conductor Size:	
Phase conductor	
Neutral conductor Grounding conductor	
(All load should be given as	s kilowatt, tons, or horsepower)
Estimated Total KW Load	2 X Service:
Charle Bloom Load	Example:
Single Phase Load A/C	Service Deposit 200 Amp \$200.00
Heating	100 Amp \$100.00
Lights	2007 mp
Receptacles	
Miscellaneous motors (7.5 HP or smaller; give combined	total)
Motors (List each individual motor 7.5 HP or larger)	
Welders	
Three Phase Load	
A/C	
Heating	
Lights	
Receptacles	
Miscellaneous motors (50 HP or smaller; give combined to	total)
Motors (List each individual motor 50 HP or larger)	
Welders	tarting parace the line veltage fligher producing
Any disturbance producing loads? (i. e., large motors st equipment, adjustable speed drives, large amount of el	
Customer planning on installing power factor correction	
If yes, how many KV ARs?	ii capacitors:
Customer	
Print & Signature	
· · · · · · · · · · · · · · · · · · ·	